



Transparent junction boxes



IP44 - IK08

Class 2

Patented components



A full range made up of 5 models : Minipak, Dynapak, Citypak, Interpak and Europak to cover different sizes of lampposts (from int. Ø 70 mm min. to int. Ø 122 mm min.).

Bottom cover easily fitted for secure maintenance of the connections.

Central locking by ¼ turn captive screw.

Open sides and stiffened back to facilitate connection.

Fixing bracket, adjustable without tools.

ADVANTAGES

A 100% transparent range.

Specifically designed for optimal and complete visibility of the inside of the junction box.

Immediately view and identification of the components.

Easy maintenance and wiring.

TECHNICAL CHARACTERISTICS

Casing

- Polycarbonate, self-extinguishing.
- IP44 in accordance with IEC 60529 (open junction box: IP2X).
- IK08 in accordance with EN 62262.
- Class 2.
- -40°C to +130°C.

Product standards

- EN 61439-2.

Installation standards

- NF C17-200 and associated guides.

Standard colour : Transparent.

Mounting :

- Fixing bracket with 1 or 2 hooks.
- Possible vertical rail mounting with M6 screws.

Optinal :

- Terminal block : marking of the terminals to facilitate maintenance.

Delivery :

- Pre-wired with high-temperature silicone-coated wires and crimped lugs.
- Supplied with configuration labels and cable clamp.

Totally transparent, complete visibility

Minipak



Available with output from the top



Dynapak



Available with output from the top



Citypak



Interpak



Europak

